

EXIDE MATRIX



- Maintenance-free batteries with advanced Ca - Ca system
- Long wet shelf life - no freshening charge required for up to 6 months from date of manufacture
- Special paste formulation for positive and negative plates - higher life expectancy with superior charge acceptance in service
- Double-clad polyethylene and glass mat separation - high reliability and longer life
- Special Omega type cover design fitted with Venturi type chamber cover - excellent spill-resistant characteristics
- Attractive cosmetics



66 Month Warranty *
(36 FOC + 30 PRO-RATA)
* T&C Apply

Technical Specifications of Exide Matrix Range of Batteries

| Battery Nomenclature | Ref C20 Capacity (Ah) | Maximum Overall Dimensions (MM) | | | Nominal Filled Weight (KG) | Electrolyte Volume (LITRES) | Charging Current (A) | CCA at -18°C As Per | | | Acid Level Indicator | Battery Layout |
|----------------------|-----------------------|---------------------------------|-----|-----|----------------------------|-----------------------------|----------------------|---------------------|-----|-----|----------------------|-------------------------|
| | | L | W | H | | | | EN | IEC | SAE | | |
| FMT0-MTRED35R | 35 | 197 | 129 | 227 | 12.1 | 2.1 | 3 | - | 270 | 332 | PRESENT | Right Layout - + |
| FMT0-MTRED35L | 35 | 197 | 129 | 227 | 12.1 | 2.1 | 3 | - | 270 | 332 | PRESENT | Left Layout + - |
| FMT0-MTRED45L | 45 | 238 | 129 | 227 | 15 | 2.9 | 3.5 | - | 330 | 410 | PRESENT | Left Layout + - |
| FMT0-MTREDDIN100 | 100 | 353 | 175 | 190 | 23.4 | 5.5 | 8 | 850 | - | - | PRESENT | Left Layout + - |