

EXIDE MILEAGE



- Robust design - to take care of stringent application requirements
- Special side vented cover design - excellent spill-resistant characteristics
- Double clad separation - high reliability and life expectancy ensures customer satisfaction
- Technology - to suit high temperature applications
- Appearance - rugged with appealing cosmetics
- Magic Eye - for determination of electrolyte level and state-of-charge
- Easy to use - batteries delivered in factory-charged, ready-to-use condition



55 Month Warranty *
(30 FOC + 25 PRO-RATA)

* T&C Apply

Technical Specifications of Exide Mileage Range of Batteries

Battery Nomenclature	Ref C20 Capacity (Ah)	Maximum Overall Dimensions (MM)			Nominal Filled Weight (KG)	Electrolyte Volume (LITRES)	Charging Current (A)	CCA at -18°C As Per			Acid Level Indicator	Battery Layout
		L	W	H				EN	IEC	SAE		
FML8-ML35R	35	197	129	227	10.6	2.2	3	-	270	332	PRESENT	Right Layout - -
FML8-ML35L	35	197	129	227	10.6	2.2	3	-	270	332	PRESENT	Left Layout - -
FML0-ML38B20L	35	197	129	227	10.5	2.2	3	-	270	332	PRESENT	Left Layout - -
FML0-ML38B20R	35	197	129	227	10.5	2.2	3	-	270	332	PRESENT	Right Layout - -
FML8-ML40LBH	40	197	137	227	11	2	3	-	280	354	PRESENT	Left Layout - -
FML0-ML40RBH	40	197	137	227	11	2	3	-	280	354	PRESENT	Right Layout - -
FML0-MLDIN50	50	207	175	190	14	2.8	4	405	-	-	PRESENT	Left Layout - -
FML8-MLDIN65LH	65	278	175	175	18.4	3.5	5	500	-	-	PRESENT	Left Layout - -

FML0-ML45D21LBH	45	205	177	222	14.3	3.2	3.5	-	330	410	PRESENT	Left Layout -■■■■■-
FML0-ML55D23L	54	231	173	223	16	3.6	4.5	-	360	450	PRESENT	Left Layout -■■■■■-
FML0-ML75D23LBH	68	231	175	223	17.3	3.5	5	-	450	565	PRESENT	Left Layout -■■■■■-
FML0-MLDIN44LH	44	210	175	175	13	2.6	3.5	360	-	-	PRESENT	Left Layout -■■■■■-
FML0-MLDIN55	55	242	175	190	16.8	3.35	4.5	480	-	-	PRESENT	Left Layout -■■■■■-
FML0-MLDIN55R	55	242	175	190	16.8	3.35	4.5	480	-	-	PRESENT	Right Layout -■■■■■,
FML0-MLDIN60	60	242	175	190	16.8	3.35	5	500	-	-	PRESENT	Left Layout -■■■■■-
FML0-MLDIN44R	44	207	175	190	13	2.9	3.5	360	-	-	PRESENT	Right Layout -■■■■■,
FML0-MLDIN80	80	315	175	190	22.8	6.2	6.5	760	-	-	PRESENT	Left Layout -■■■■■-
FML0-MLDIN66	66	278	175	190	20.1	3.8	5	590	-	-	PRESENT	Left Layout -■■■■■-